

CAM-TYPE CONNECTORS (UP TO 400A, 600V)

16 Series, Taper Nose  

Description	Color	Cat. No.	Cat. No.	Cat. No.
		Complete	Contact	Insulator
Male Detachable Plug - Double Set Screw (Cable Size: 1/0-4/0)	White	16D24-W	16D24-C	16SDM-14W*
	Grey	16D24-GY	16D24-C	16SDM-14GY*
	Black	16D24-E	16D24-C	16SDM-14E*
	Brown	16D24-H	16D24-C	16SDM-14H*
	Red	16D24-R	16D24-C	16SDM-14R*
	Blue	16D24-B	16D24-C	16SDM-14B*
	Orange	16D24-O	16D24-C	16SDM-14O*
	Green	16D24-G	16D24-C	16SDM-14G*
	Yellow	16D24-Y	16D24-C	16SDM-14Y*
	Female Detachable Plug - Double Set Screw (Cable Size: 1/0-4/0)	White	16D33-W	16D33-C*
Grey		16D33-GY	16D33-C*	—
Black		16D33-E	16D33-C*	16SDF-14E
Brown		16D33-H	16D33-C*	16SDF-14H*
Red		16D33-R	16D33-C*	16SDF-14R
Blue		16D33-B	16D33-C*	16SDF-14B*
Orange		16D33-O	16D33-C*	16SDF-14O*
Green		16D33-G	16D33-C*	16SDF-14G*
Yellow		16D33-Y	16D33-C*	16SDF-14Y*



16D33-O




16D24-E

* Contact factory for availability.


TESTING AND CODE COMPLIANCE

- Meets UL Standards (File #E13399)
- NEMA 3R-Rated (rainproof) for use outdoors
- CSA Certified (File #152105)

DIMENSIONS



Male Detachable Plug – Double Set Screw



Female Detachable Plug – Double Set Screw