

170-03006



Article Number: 170-03006

Description: Expandable Braided Sleeving, Flame Retardant, 1/4" Dia., PET, BK, 200.0 ft/Reel

Base Data	Local Order Number	170-03006
	Type	BSPFR140
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. • Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Expandable Braided Sleeving, Flame Retardant, 1/4" Dia., PET, BK, 200.0 ft/Reel
Product Dimensions	Length L (Imperial)	200.0ft
	Length L (Metric)	61.0m
	Reel Length (imperial)	200.0ft
	Bundle Diameter Min. (Imperial)	0.125"
	Bundle Diameter Min. (Metric)	3.2mm
	Bundle Diameter Max. (Imperial)	0.437"
	Bundle Diameter Max. (Metric)	11.1mm
	Nominal Diameter (Imperial)	1/4"
	Nominal Diameter (Metric)	6.4mm
Material and Specifications	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	UL94 V0

170-03006



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200.0ft
	Package Quantity (Metric)	200.0ft
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.48lbs
	Weight (Metric)	0.22kg