

170-03024



**Article Number:** 170-03024

**Split Wrap Braided Sleeve, 0.5" ID, PET, Black, 75.0 ft/Standard Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03024

**Type** BSPSW120

**Color** Black (BK)

**Features and Benefits**

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Product Description** A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

**Open Post Termination** No

**Short Description** Split Wrap Braided Sleeve, 0.5" ID, PET, Black, 75.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 75.0 ft

**Length L (Metric)** 22.9 m

**Bundle Diameter Max. (Imperial)** 0.5 "

**Bundle Diameter Max. (Metric)** 12.7 mm

**Nominal Diameter (Imperial)** 1/2 "

**Nominal Diameter (Metric)** 12.7 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity (Imperial)** 75 ft

**Package Quantity (Metric)** 75.0 ft

**Reel Length (imperial)** 75.0 ft

**Reel Length (metric)** 22.9 m

**Weight (Metric)** 0.48 kg

**Weight (imperial)** 1.05 lbs

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL94 V0

**Melting Point** +250 °C

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS compliant (Article 4 - 1)** Yes

**UL Recognized (US and Canada)** Yes