

170-03037



Article Number: 170-03037

Split Wrap Braided Sleeving, 0.25" ID, PET, Black, 100.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03037

Type BSPSW140

Color Black (BK)

Features and Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Product Description A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Open Post Termination No

Short Description Split Wrap Braided Sleeving, 0.25" ID, PET, Black, 100.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Bundle Diameter Max. (Imperial) 0.25 "

Bundle Diameter Max. (Metric) 6.4 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.4 mm

Logistics and Packaging

Quantity Per box

Package Quantity (Imperial) 100 ft

Package Quantity (Metric) 100.0 ft

Reel Length (metric) 30.5 m

Reel Length (imperial) 100.0 ft

Weight (Metric) 0.27 kg

Weight (imperial) 0.6 lbs

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Melting Point +250 °C

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS compliant (Article 4 - 1) Yes

UL Recognized (US and Canada) Yes