

170-03071

HellermannTyton

Article Number: 170-03071

Description: Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel



Base Data	Local Order Number	170-03071
	Type	BSPFR188
	Color	Gray (GY)
	Features and benefits	<ul style="list-style-type: none"> • Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. • Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		68.6m
Reel Length (imperial)		225.0ft
Bundle Diameter Min. (Imperial)		0.094"
Bundle Diameter Min. (Metric)		2.4mm
Bundle Diameter Max. (Imperial)		0.25"
Bundle Diameter Max. (Metric)		6.4mm
Nominal Diameter (Imperial)		1/8"
Nominal Diameter (Metric)		3.2mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	FAR 25

170-03071



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	225ft
	Package Quantity (Metric)	68.58m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.4lbs
	Weight (Metric)	0.18kg