

170-03071

Article Number: 170-03071

Flame Retardant Expandable Braided Sleeving, 0.13" Dia., Gray, 225.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03071

Type BSPFR188

Color Gray (GY)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Open Post Termination No

Short Description Flame Retardant Expandable Braided Sleeving, 0.13" Dia., Gray, 225.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 225.0 ft

Length L (Metric) 68.6 m

Bundle Diameter Min. (Imperial) 0.094 "

Bundle Diameter Min. (Metric) 2.4 mm

Bundle Diameter Max. (Imperial) 0.25 "

Bundle Diameter Max. (Metric) 6.4 mm

Nominal Diameter (Imperial) 1/8 "

Nominal Diameter (Metric) 3.2 mm

Logistics and Packaging

Quantity Per reel

Package Quantity (Imperial) 225 ft

Package Quantity (Metric) 225.0 ft

Reel Length (imperial) 225.0 ft

Reel Length (metric) 68.6 m

Weight (Metric) 0.18 kg

Weight (imperial) 0.4 lbs

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability VW-1
Mil-202
FMVSS 302
FAR 25

Melting Point +250 °C

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS compliant (Article 4 - 1) Yes

UL Recognized (US and Canada) Yes