

170-03141



Article Number: 170-03141

Flame Retardant Split Wrap Braided Sleeving, 0.25" ID, Black, 200.0 ft/Bulk Reel



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03141

**Type** BSSWFR140B

**Color** Black (BK)

**Features and Benefits**

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Product Description** A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

**Short Description** Flame Retardant Split Wrap Braided Sleeving, 0.25" ID, Black, 200.0 ft/Bulk Reel

## Product Dimensions

**Length L (Imperial)** 200.0 ft

**Length L (Metric)** 61.0 m

**Reel Length (imperial)** 200.0 ft

**Bundle Diameter Max. (Imperial)** 0.25 "

**Bundle Diameter Max. (Metric)** 6.4 mm

**Nominal Diameter (Imperial)** 1/4 "

**Nominal Diameter (Metric)** 6.4 mm

## Logistics and Packaging

**Quantity Per** box

**Package Quantity** 200 ft

**Package Quantity (Metric)** 200.0 ft

**Weight (Metric)** 0.54 kg

**Weight (imperial)** 1.2 lbs

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** FAR 25  
VW-1

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes

**UL Recognized (US)** Yes