

170-03175



**Article Number:** 170-03175

**Aluminum Laminated Fiberglass Sleeving, 0.38" Dia., Silver, 100.0 ft/Standard Reel**



Download drawing



Download spec sheet



Download tech sheet

## Base Data

**Local Order Number** 170-03175

**Type** BSHTTST38SR

**Color** Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
  - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
  - Cuts with ordinary scissors for fast, easy application.

**Product Description** A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

**Short Description** Aluminum Laminated Fiberglass Sleeving, 0.38" Dia., Silver, 100.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Bundle Diameter Max. (Imperial)** 0.437 "

**Bundle Diameter Max. (Metric)** 11.1 mm

**Diameter D (imperial)** 0.38 "

**Diameter D (metric)** 9.7 mm

**Nominal Diameter (Imperial)** 3/8 "

**Nominal Diameter (Metric)** 9.7 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100 ft

**Package Quantity (Metric)** 1

**Reel Weight (Metric)** 1.02 kg

**Reel Weight (Imperial)** 2.25 lbs

## Material and Specifications

**Material** Glass Fiber (GF)  
Aluminium (AL)

**Flammability** non flammable

**Operating Temperature** -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes

---

© HellemannTyton 2015