1. CONDUCTOR:

1.1 Size and Material: 22 AWG, 19 strands, nickel-plated copper wire.

2. INSULATION:

- 2.1 Extruded PFA.
- 2.2 Wall thickness: .013" nom.
- 2.3 Marking on the insulation: as per UL and CSA Standards.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:


3.1 Voltage rating: 300 VAC R.M.S.
3.2 Temperature rating: 250°C

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 1726.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: .			
Date:			



UNCONTROLLED DOCUMENT
A later revision of this specification may exist.

ication is the prop

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

er of The Marmon

A member of The Marmon Group of companies

Date:

July 22, 2008

Scale:

Verified:

Size:

Date:

July 22, 2008

1 of 1



1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

Code Ident. No:

57104

XPA13N2219/34-X

F02462-X

Wire & Cable Specification - HBR.04.86.D