1. CONDUCTOR:

- 1.1 Size and Material: 12 19/.0185" AWG nickel-plated copper wire.
- 1.2 O.D.: .0885" nom.

2. INSULATION:

- 2.1 Extruded PFA.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .1285" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
 3.2 Temperature rating: 250⁰C

4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 1727.
- 4.2 CSA Standard C22.2 No.210.2-M90 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _			
Date:			

Engineering Change Notice No.		lare Alk					
		July 1, 2004		- Harbour INDUSTRIES 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3			
	This specification is the property of Harbour Industries Canada Limited and may not be used or	Verified	<u> </u>	ate	Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com		
	copied without the express written permission of Harbour Industries Canada Limited.	Datas	cam	all	Description:		
		July 1, 2004		XPA20N1219/0185-X			
UNCONTROLLED DOCUMEN		Size:	TScale:	P	Cale Idel. No.	SecificationNo:	Rev.
A later revision of this specification may exist.	A member of The Marmon Group of companies			1 of 1	57104	F03573-X	ification-IBR.04.86D