

Aerospace Part#: 1751pv

PLENUM CABLE

DESCRIPTION

7 Conductors AWG 18/7x26 TC
Unshield CL2P CMP FEP/PVC Natural

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
7	18/7x26	Tinned Copper	FEP	.007"	.062"

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
LS PVC	Natural	.015"	.216" Nom.	3"-4" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -5C to 75C	51.8 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 300V Power Ltd.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor
Resistance	Sunlight
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

MISCELLANEOUS

Markings: TYPE CL2P - TYPE CMP 18 AWG (UL), C(UL) 75C E130356 ROHS

Color Code: Black / Red / White / Green / Brown / Blue / Orange /

Contact Us For More Information

T: 800.395.0200 **F:** 718.358.2522 **E:** sales@aerospacewire.com **W:** www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice