



VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

CONNECTOR: PHX707 A
COLOR: BLACK

- NOTES:
- 1) CORDAGE: 18/2/SPT-1/105°C/BLACK
 - 2) APPROVALS: UL/CSA WIRING HARNESS.
 - 3) RATING: 1 AMP/250 VOLTS
 - 4) FLAME RATING : VW1
 - 5) CORDAGE DIMENSIONS: .110" X .220" REF.
 - 6) CORD IS NOT POLARIZED. RIBBED LEAD WILL NOT ALWAYS BE IN SAME POSITION WITH REFERENCE TO THE CONNECTOR.
 - 7) PACKAGING: 100 PIECES PER CARTON.
 - 8) ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

REV	SCALE:	NDT TO SCALE	ECD:	ITEM DESCRIPTION	DESCRIPTION	DATE
1			N/A	C.U.D - NEW RELEASE		5/26/05

Proprietary Notice:
This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

MATERIAL:
PLUG: PVC, BLACK
JACKET: PVC, BLACK

FINISH:

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ± .005
.XX ± .02
.X ± .03
FRACT. ± 1/32
ANGULAR ± 1/2°



CUD

- Indianapolis, IN
- Conover, N.C.
- Freemont, CA
- Aguascalientes, MX
- Tijuana, Mexico
- Hermosillo, MX
- Clinton, AR
- Kanata, Canada

APPROVED	DRAWN BY	DATE:
	STC	5/26/05

PART NO. 17903 10 B1