



For more Information  
please call

1-800-Belden1



### General Description:

Video Cable, Plenum-CMP, RG6, 18 AWG solid bare copper, foam FEP insulation, Duofoil®+85% tinned copper braid, Flamarrest® jacket

### Usage (Overall)

Suitable Applications: Commercial Video

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	18	Solid	BC - Bare Copper	1.016

Total Number of Conductors: 1

#### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (mm)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	4.267

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duobond® II	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	TC - Tinned Copper	85.000

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 5.867 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 49.855 Kg/Km

Max. Recommended Pulling Tension: 284.685 N

Min. Bend Radius/Minor Axis: 63.500 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 11/22/2011

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

## 1369P Coax - System Integrators Video Cable

MII Order #39 (China RoHS): Yes

RG Type: 6/U

### Flame Test

UL Flame Test: NFPA 262

CSA Flame Test: FT6

### Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: No

### Plenum/Non-Plenum

Plenum (Y/N): Yes

Non-Plenum Number: 1369R

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

75

### Nom. Inductance:

Inductance (µH/m)

0.337943

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

53.480

### Nominal Velocity of Propagation:

VP (%)

83.000

### Nominal Delay:

Delay (ns/m)

4.003

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

20.9984

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

11.812

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.787
3.580	1.476
5.000	1.805
7.000	2.133
10.000	2.461
67.500	5.709
71.500	5.840
88.500	6.365
100.000	6.890
135.000	7.874
143.000	8.203
180.000	9.187
270.000	11.155
360.000	13.124
540.000	17.061
720.000	20.014
750.000	20.342
1000.000	23.951
1500.000	30.185
2000.000	35.763
2250.000	38.060
3000.000	44.950

### Max. Operating Voltage - UL:

Voltage

300 V RMS

## METRIC MEASUREMENT VERSION

### 1369P Coax - System Integrators Video Cable

**Other Electrical Characteristic 1:**

Impedance tested in accordance with AS 1 M D 4566 - 05 paragraph 48.2, option 2 using a 75 Ohm fixed bridge and termination.

**Other Electrical Characteristic 2:**

Return Loss tested in accordance with ASTM D 4566 - 05 paragraph 50.3, using a 75 Ohm fixed bridge and termination.

**Minimum Return Loss:**

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	3000.000	15.000

#### Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1369P N3U1000	1,000 FT	35.000 LB	GREEN, MIL		#18 FFEP SH FLRST
1369P N3U500	500 FT	13.500 LB	GREEN, MIL		#18 FFEP SH FLRST
1369P 0011000	1,000 FT	35.000 LB	BROWN		#18 FFEP SH FLRST
1369P 001500	500 FT	13.500 LB	BROWN		#18 FFEP SH FLRST
1369P 0021000	1,000 FT	35.000 LB	RED		#18 FFEP SH FLRST
1369P 002500	500 FT	13.500 LB	RED		#18 FFEP SH FLRST
1369P 0031000	1,000 FT	35.000 LB	ORANGE		#18 FFEP SH FLRST
1369P 003500	500 FT	13.500 LB	ORANGE		#18 FFEP SH FLRST
1369P 0041000	1,000 FT	35.000 LB	YELLOW		#18 FFEP SH FLRST
1369P 004500	500 FT	13.500 LB	YELLOW		#18 FFEP SH FLRST
1369P 0061000	1,000 FT	35.000 LB	BLUE, LIGHT		#18 FFEP SH FLRST
1369P 006500	500 FT	13.500 LB	BLUE, LIGHT		#18 FFEP SH FLRST
1369P 0071000	1,000 FT	35.000 LB	VIOLET		#18 FFEP SH FLRST
1369P 007500	500 FT	13.500 LB	VIOLET		#18 FFEP SH FLRST
1369P 0081000	1,000 FT	35.000 LB	GRAY		#18 FFEP SH FLRST
1369P 008500	500 FT	13.500 LB	GRAY		#18 FFEP SH FLRST
1369P 0091000	1,000 FT	35.000 LB	WHITE		#18 FFEP SH FLRST
1369P 009500	500 FT	13.500 LB	WHITE		#18 FFEP SH FLRST
1369P 0101000	1,000 FT	35.000 LB	BLACK		#18 FFEP SH FLRST
1369P 010500	500 FT	13.500 LB	BLACK		#18 FFEP SH FLRST

Revision Number: 2    Revision Date: 04-30-2013

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.