



**Description:** Two Conductor, 18 AWG  
 with a PVC Jacket

**Date:** 8/5/2014

**JM Part Number:** JM57270  
**Reference:** 1802C-8JM1

**Components** Two 18 AWG Insulated Conductors

Conductor: 18 AWG, 16/30 tinned copper

Insulation: .016" nominal wall of PVC (see color code) .077"

**Cable Construction**

Cabling: Two insulated conductors twisted together with FR PP Fillers

Jacket: .020" nominal wall of Gray PVC .194" (.206" Max)

**Color Code**

- 1. Red
- 2. Black

**Surface Print - Inkjet**

E138031 2/C 18 AWG 75C (UL) TYPE CM OR AWM 2509 80C 300V ---  
 LL41103 CSA TYPE CMG 60C FT4 --- CE ROHS

**Requirements**

Temperature: 80C  
 Voltage: 300V

Approvals: UL Type CM  
 AWM Style 2509  
 CSA Type CMG  
 CE-LVD & RoHS Compliant (2011/65/EU)

|             |     |          |        |         |
|-------------|-----|----------|--------|---------|
| Written By: | scs | 8/5/2014 | Rev. 0 | Initial |
| Revised By: |     |          |        |         |
| Revised By: |     |          |        |         |
| Revised By: |     |          |        |         |