


232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website; www.dataguidecable.com



**2 CONDUCTORS 18 AWG OVERALL SHIELD
 TPU JACKET 80C 300VOLT**

CONDUCTORS

- 18 AWG (16x30) Tinned Annealed Copper Insulated with .009" Nominal Wall of PVC to a Nominal O.D. of .070" +/- .002"
- 2 Conductors Total
- Color Coded as Indicated

NOTES:

- .0013" Nominal Thickness Aluminum/Polyester Tape Shield, Foil Facing In
- 18 AWG 16/30 Tinned Copper Drain Under Foil Shield
- .001" Nominal Thickness Tissue Separator Tape Pulled Under Jacket
- .035" Nominal Wall Thickness Blue Polyurethane "Pressure" Jacket to .225" Nominal Final Diameter +/- .005"
- Surface Printed in Black Ink to UL AWM and CSA AWM as Follows:
 "E90298 AWM 20233 80C 300V - - LL91737 CSA AWM I/II A/B 80C 300V FT1"

COLOR CODE

CONDUCTOR	COLOR
1	BLUE
2	WHITE

AGENCY APPROVAL

- RoHS Approved Construction

REVISION HISTORY

0	5/08/13	WD	INITIAL RELEASE

Customer P/N	
D.G. Part Number	13E1-5
Prepared By:	KAM
Reviewed By:	WJD