


- CONDUCTORS** -18 AWG (16/30) BARE ANNEALED COPPER INSULATED WITH .016" NOMINAL WALL OF POLYETHYLENE TO A NOMINAL O.D. OF .078.
- 2 CONDUCTORS TOTAL
 - COLOR CODE: BLACK AND NATURAL(CLEAR)



- .0012" NOMINAL THICKNESS ALUMINUM/POLYESTER BINDER TAPE SHIELD, FOIL SIDE FACING OUTWARD
- 20 AWG 10/30 TINNED COPPEWR DRAIN OVER TAPE SHIELD
- .020" NOMINAL WALL THICKNESS "GRAY" LEAD FREE PVC JACKET TO .200" NOMINAL FINAL DIAMETER
- SURFACE PRINTED IN BLACK INK TO UL AND CSA AS FOLLOWS:
 "E123820 18 AWG TYPE CM (UL) 75C OR AWM 2092 --
 LL91737 CSA TYPE CMG"
- THIS CABLE IS "ROHS" COMPLIANT

DATA GUIDE		ONE ERNRIC PLACE 560 MAIN STREET GARDNER, MA 01440 978-632-0900	
CABLE CORP.		TITLE 2C 18AWG FOIL SHIELED PE/PVC UL/CSA/ROHS	
SCALE N/A	P/N 07J25-8	REV	
DATE 9/07	DRN. BY WJD	APP. BY	

REV.	DESCRIPTION	DATE	APP.
1	INITIAL RELEASE	9/26/07	