

Specifications:



- UL Listed, NEC Type CM or CL2, 75°C
- UL AWM Style 2095, 80°C, 300V
- CSA Certified PCC FT-4

Description:

Each Conductor Stranded or Solid Tinned Copper,
 Color Coded Polyvinylchloride Insulation,
 Spiral Wrapped Bare Copper Shield -
 95% Shield Coverage.
 Nom. .020" Gray Polyvinylchloride Jacket Overall.

[*Click on a part number below for pricing and ordering online](#)

WEICO NO.	NO. OF COND.	CONDUCTOR AWG	STRAND	NOM. INS. THICKNESS (INCHES)	UL NEC RATING	NOM. O.D. (IN)
9301	2	22	Solid	.016	CM	.170
9302*	1	22	7/30	.016		.115
9303	2	22	7/30	.016	CM	.175
9304	3	22	7/30	.016	CM	.190
9305	4	22	7/30	.016	CM	.200
9306	6	22	7/30	.016	CM	.235
9307*	1	20	10/30	.016		.130
9308	2	20	10/30	.016	CL2	.195
9309	3	20	10/30	.016	CL2	.210
9310	4	20	10/30	.016	CL2	.225
9311	6	20	10/30	.016	CL2	.265
9312*	1	18	16/30	.016		.135
9314	2	18	16/30	.016	CM	.230
9315	3	18	16/30	.016	CM	.235
9316	4	18	16/30	.016	CM	.245
9317	2	16	26/30	.016	CL2	.240
9318	3	16	26/30	.016	CL2	.245
9319	2	14	41/30	.020	CL2	.285
9320	3	14	41/30	.020	CL2	.290

*Single Conductor Cables UL AWM Style 1108, 80°C, 300 V, VW-1

COLORS		
1 - Black	3 - White	5 - Yellow
2 - Red	4 - Green	6 - Blue

Standard Put-Ups: 1000 ft., 500 ft., 1000ft