

Audio-Control-Instrumentation. 1 Pair 18awg, Shielded Plenum Cable

39902P
DRAWING NO.

Part No.	39902P
CONDUCTOR	18 awg (7 x 0.0159") Tinned Copper O.D.: 0.046" (1.17 mm)
CONDUCTOR RESISTANCE	6.45 Ohms/Mft (21.16 Ohms/km)
RESISTANCE UNBALANCE	5% Maximum
INSULATION	0.008" (0.20 mm) Plenum Polyvinylchloride (PVC) O.D.: 0.063" (1.60 mm)
LAY LENGTH	0.44"
SHIELD	Aluminum/Mylar Tape
DRAIN WIRE	20 awg (7 x 0.0126") Tinned Copper
RIPCORD	Polyester Ripcord Under Jacket
JACKET	0.015" (0.38 mm) Plenum Polyvinylchloride (PVC)
OVERALL DIAMETER	0.164" (4.17 mm)
CAPACITANCE	55 pF/ft (180 pF/m)
IMPEDANCE	40 Ohms
VELOCITY OF PROPAGATION	57%
WEIGHT	23.5 lbs/Mft (35 kgs/km)
FLAME RATING	FT6
APPROVALS	CSA CMP

ALL DIMENSIONS NOMINAL UNLESS SPECIFIED

REVISION	APPD	DATE
A	<i>AA</i>	1/22/03



DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6

DRWN	CB	DATE
		06/23/99
CHKD	<i>AA</i>	06/24/99
APPD	<i>GS</i>	06/24/99