

232 Sherman Street Gardner, MA 01440 Phone: 978-632-0900 Fax: 978-630-1872 Visit us on our website; www.dataquidecable.com

3 CONDUCTORS 18 AWG UNSHIELDED TPU JACKET 80C 300VOLT

CONDUCTORS:

- 18 AWG (16x30) Tinned Annealed Copper Insulated with .009" Nominal Wall of PVC to a Nominal O.D. of .070" +/- .002"
- 3 Conductors Total
- Color Coded as Indicated

NOTES:

- .001" Nominal Thickness Tissue Separator Tape Pulled under Jacket
- .035" Nominal Wall Thickness Black Polyurethane "Pressure" Jacket to .225" Nominal Final Diameter +/- .005"
- Surface Printed in White Ink to UL AWM and CSA AWM as Follows: "E90298 AWM 20233 80C 300V - LL91737 CSA AWM I/II A/B 80C 300V FT1"

COLOR CODE

CONDUCTOR	COLOR
1	WHITE
2	RED
3	BLACK

AGENCY APPROVAL

- Rohs Approved Construction

REVISION HISTORY

Customer Number			
D.G. Part Number	13E1-6		
Prepared By: KAM			
Reviewed By: WJD			

0	5/8/13	WD	INITIAL RELEASE