

Part Number: 92359A

Revision Level: 0

Date: 3/9/2009

3C 18 16/30 TC PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#18 AWG 16/30 Tinned Copper	0.048" nom.
Insulation:	0.015" Wall Polyvinyl Chloride	0.078" nom.
Cable:	3 conductors	0.172" nom.
Jacket:	0.032 Wall Polyvinyl Chloride	0.236" +/- 0.012"
Print Legend:	<i>CAROL (R) 18 AWG -- 92359A -- 75C E111240-8 CM (UL) C (UL) OR STYLE 2464/2576 --- CSA LL69381 CMG 60C -- MADE IN USA (DATE CODE)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM (UL) C (UL)
CSA International	Type CMG
UL Subject 758	AWM Style 2464/2576

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V _{rms}
CONDUCTOR D.C. RESISTANCE:	7.2 Ohms/1000 ft. nom. @ 20 C
MUTUAL CAPACITANCE:	28.0 pF/ft.

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Red
2	Green
3	Black