

Specification

US North Central

5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 3/28/2013

Issue: 1

Construction

Descripti	n: 3 Cond 18(16) TC AWM-2661 Yellow PVC Jacket				Diam. (In)
Component:	3 Conductors				•
Conductor:	18 16/30 TC to AS	18 16/30 TC to ASTM B 33-74			
Insulation:	0.01" P	remium Grade PVC		·	0.068"
Color Code:	To be determined	To be determined			
Cable					
Assembly:	3 Conductors Bund	3 Conductors Bunched Cabled			
Tape:	Clear Mylar Tape	Clear Mylar Tape			
Jacket:	0.03" AW	/M Recognized PVC	Jacket		0.2092"
Jacket Color:	Yellow				0.2092"
Print:	E174416 RU AWM 2661 1	05℃ 300V VW-1 cU	R I/II A 105° C 300 V F	T-1 3 Cond #18	
Specifications:					
UL	AWM - 2661	105℃	300 Volt	VW-1	
Canadian cUR	AWM	105℃	300 Volt	FT-1	

Environmental Compliance

EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.