

# BAROSTAT II 150V Cable

Polypropylene/PVC 60°C BAROSTAT II CMH 150V FT1 Cable



Image not to scale or color & for reference only. See Table 1 for Dimensions

## CONSTRUCTION:

**Conductors:** Solid, Bare Copper per ASTM B3 and B33

**Insulation:** PP - Color Code: Red, White, Green

**Assembly:** The insulated conductors are pulled under the jacket without cabling. A rip cord is added to the assembly to facilitate overall jacket removal.

**Jacket:** PVC - Brown

## SPECIFICATIONS:

- ASTM B3, B174
- UL 13 - CL2
- CSA C22.2 No. 210 - CMH

## SAMPLE PRINT LEGEND (White Inkjet Print):

TYPE CL2 C(ETL)US 18 AWG 3/C BAROSTAT II SUN RES -- TYPE CMH FT1 -- {MM/DD/YY} {HH:MM}

### TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (mils)	Jacket Thickness (mils)	Nominal OD (mils)	Nominal Weight (Lbs/Mft)
641688	18	3	1	6	14	140	28

All dimensions are nominal and subject to normal manufacturing tolerances



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | [www.southwire.com](http://www.southwire.com)

Copyright © 2020 Southwire Company, LLC. All Rights Reserved

