



**Description:** Three Conductor, 18 AWG  
 Overall PVC Jacket

**Date:** 1/18/2010

**Part Number:** JM55944

**Reference:** W1194

**Components** Three 18 AWG Insulated Conductors

Conductor: 18 AWG, 16/30 bare copper

Insulation: .016" nominal wall of PVC .077"

Release Agent: Release agent applied to prevent bonding of conductors to jacket

**Cable Construction**

Cabling: Three insulated conductors twisted together, no fillers

Jacket: .047" nominal wall of pressure extruded Gray PVC .260" ± .010"

**Color Code**

1. Black

2. White

3. Green

**Print**

Jacket to be printed with Royal Blue Ink ink as follows:

**CANFIELD CONNECTOR W1194 18/3 E66440 9A AWM 2587 90C 600V VW-1  
 LL41103 CSA AWM I/II A/B 90C 600V FT4**

**Requirements**

Temperature: 90C  
 Voltage: 600V

Approvals: UL AWM Style 2587, VW-1  
 CSA AWM, FT4

Written By:	rjc	1/18/2010	Rev. 0	Initial Issue
Revised By:	scs	1/27/2010	Rev. 1	Added JM Number
Revised By:	scs	2/15/2010	Rev. 2	Revised CSA voltage in print legend
Revised By:	rjc	4/15/2014	Rev. 3	Revised Spec To Meet CSA Minimum Jacket Requirements