

Comtran Cable LLC 330A Turner Street South Attleboro, MA 02703-7714 (P) 508-399-7004 (F) 508-399-7360 www.ComtranCorp.com

Design SpecificationPart Number: 34843

DESCRIPTION: 18 AWG 3 conductor plenum communications cable Nom. O.D. (in.)

CONSTRUCTION:

Conductors: 18 AWG 7 strand bare copper

Insulation: 0.0073" nominal wall Comflex Plenum PVC .060

Core Assembly: 3 conductors cabled together with a 3.5" nominal left hand lay

Jacket: 0.014" nominal wall White Comflex Plenum PVC .158

Parallel ripcord located under jacket

COLOR CODE: Black, White, Red

SPECIFICATIONS: UL 13, Power Limited Circuit Cable

UL 444, Communication Cables

UL 1424 Power Limited Fire Alarm Cable NFPA 262, Plenum Flame Test (UL 910)

NEC Article 725, 760 and 800

CERTIFICATIONS: UL Listed Type CL3P/FPLP

UL and cUL Listed Type CMP

California State Fire Marshal Approved

ELECTRICAL CHARACTERISTICS:

Capacitance: 20 pF/ft nominal conductor to conductor @ 1 KHz

DC Resistance: 6.79 ohms/Kft max @ 20C

SURFACE PRINT: E111272 (01-12345) 18 AWG CL3P/FPLP (UL) OR CMP C(UL)US RoHS

Sequential footage markers every 2 feet

DRAWING	REV.	Date	DRWN.	APP.	REMARKS	
						34843
4843	.04	06/02/06	2me	RHW	Add ripcord;revise print	
4843	.03	05/27/03	2me	RHW	Revised and redrawn	Dogo 1 of 1
4843	.02	01/28/03	2me	RHW	Revised and redrawn	Page 1 of 1