



## PRODUCT SPECIFICATION

February 6, 2013

Roger McConnell  
PKC Group

Part Number: 9(19318(4-5-6)SF)

Conductor: 0.045" 18AWG 19(S) Silver Plated Copper

Insulation: 0.010" Nom. of 200°C Extruded Polytetrafluoroethylene (PTFE)

# Of Conductors: 3

Color Code: 6 – Blue  
4 – Yellow  
5 – Green

Construction: Three conductors twisted together.

Shield: Aluminum/Mylar tape, 100% coverage

- Foil Facing In
- 0.039" 20AWG 7(S) Tin Plated Copper Drain

Jacket: 0.010" Nom. of White 200°C Extruded Polytetrafluoroethylene (PTFE)

Nominal OD: 0.164"

Temp. Rating: 200°C

Voltage: 600 Volts

RoHS Compliant: Yes

(UL) Style: N/A

Shipping Tolerance: +/- 10%

Phone (860) 589-9035

[www.multicable.com](http://www.multicable.com)

Fax (860) 589-7520

This specification is proprietary information Owned by Multi/Cable Corporation and is submitted under a confidential relationship and may not be used or disclosed except for uses expressly granted by Multi/Cable. The information above is provided in good faith. It is believed to be accurate and represents the best information currently available to us. We make no warranty of merchantability, fitness for a particular purpose or of any other type, express or implied, with respect to products described or data or information provided, and we assume no liability resulting from such products, data or information. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the products, and must be familiar with and follow generally accepted safe handling procedure. All dimensions herein are nominal.