

Description: 18 AWG 3/C STR OAS CMP-CL2P
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 18 AWG 19/0.0092" Stranded Bare Copper
Insulation Plenum PVC
Insulation Thickness 0.008" nom.
Insulation Colors Blk,Wht,Red
Insulation Diameter 0.060 nom.
Lay Length 2.5" nom.
Drain Wire 24 AWG 7/32 Tinned Copper
Shield .001" Thick Aluminum/Mylar

Jacket PVC
Jacket Color Natural
Jacket Thickness 0.015" nom.
Outside Diameter 0.164" nom.

Legend (Ink Print) HONEYWELL P/N 3226 3C18 SHIELDED 3038058 (ETL) CL2P OR CMP C(ETL)US FT6
(RoHS) W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

+

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 60 pf/ft nom.
Impedance 34 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, CSA FT6