

AEROSPACE WIRE & CABLE, INC.  
 129-09 18TH AVENUE  
 COLLEGE POINT, NY 11356  
 (718) 358-2345  
 FAX (718) 358-2522

CABLE SPECIFICATIONS

|                  |   |  |             |             |
|------------------|---|--|-------------|-------------|
| CUSTOMER         | : |  | SHIP DATE : |             |
| PART NUMBER      | : | 1350/19  | QUANTITY :  |             |
| 1) DESCRIPTION   | : | 3 Cond. Shielded CL2P CMP<br>AWG 18/19x30 TC FEP/FEP   |             |             |
| 2) CONDUCTOR     | : | AWG 18/19x30 Tinned Copper                             | O.D.=       | .047"       |
| 3) INSULATION    | : | FEP .007" wall   | O.D.=       | .061"-.063" |
| 4) COLOR CODE    | : | Black / Red / White                                    |             |             |
| 5) TWIST LAY     | : | 4" Lay on Cable  |             |             |
| 6) SHIELD        | : | Aluminum / Mylar Shield with AWG 20/7x28 TC Drain Wire |             |             |
| 7) BRAID         | : | none   |             |             |
| 8) JACKET        | : | Gray FEP .010" wall                                    | O.D.=       | .155" nom.  |
| 9) MARKING       | : | E111036 TYPE CL2P-E130356 TYPE CMP 18 AWG (UL),C(UL)   |             |             |
| 10) CAPACITANCE: |   | 40.4 pF/foot nom.                                      |             | FEP/FEP     |
| 11) WEIGHT       | : | 28 lbs / 1000 feet                                     |             |             |

~~12) TEMPERATURE: Operating: -50C to 200C VOLTAGE: UL 300V Power Ltd~~