



Description: Three 18 AWG Conductors  
 Overall Foil Shield and PVC Jacket

Date: 9/6/2013

JM Part Number: TBD  
 Reference: TBD

**Components** Three 18 AWG Insulated Conductors

Conductor: 18 AWG, 7/0152 tinned copper

Insulation: .016" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .088"

**Cable Construction**

Cabling: Three insulated conductors cabled together

Shield: Aluminum-Mylar tape, Aluminum side OUT

Drain Wire: 20 AWG, 7/28 tinned copper

Jacket: .047" nominal wall of Gray PVC .288"

**Print**

E73202 3/C 18 AWG (UL) TYPE TC-ER 90C DRY 75C WET 600V SUN RES DIR BUR  
 OR C(UL) CIC-TC PVC/N FT4 --- LL41103 CSA AWM I/II A/B 90C 600V FT4

**Color Code**

1. Black 2. White 3. Red

**Requirements**

Temperature: 90C  
 Voltage: 600V

Approvals: UL Type TC  
 C(UL) CIC-TC FT4  
 CSA AWM FT4  
 Sunlight Resistant  
 Direct Burial  
 Materials are RoHS Compliant

*Woodward Hansen*  
 4/9/14

Written By:	rjc	9/6/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				