



canfield connector

SPECIFICATION FOR W1103 EUROPEAN MULTI-CONDUCTOR CABLE

1. APPLICATION IS PRIMARILY FOR INTERCONNECTION OF ELECTRONIC EQUIPMENT, INCLUDING PROXIMITY SWITCHES, CONNECTORS, AND TIMERS. IT CAN ALSO BE USED FOR REMOTE CONTROL, INSTRUMENTATION, ETC.
2. CONDUCTORS ARE TO MEET THE FOLLOWING CRITERIA:
 - A. 18 AWG
 - B. 16x30 STRANDING
 - C. COMPOSED OF FULLY ANNEALED BARE COPPER
3. JACKET IS TO BE BLACK PUR
4. COLOR CODE IS TO BE BROWN, BLUE, YELLOW/GREEN, AND BLACK.
5. INSULATED CONDUCTORS ARE TO BE CABLED AND TWISTED.
6. THE RELEASE AGENT IS TO BE TALC. NO TISSUE IS TO BE USED IN THE PRODUCTION OF THIS WIRE.
7. JACKET IS TO BE PRESSURE EXTRUDED. THE JACKET SHOULD BE FLOODED AROUND THE INSULATORS. THE OUTSIDE JACKET MUST BE ROUND.
8. 1000 FOOT SPOOLS, WHICH MEET OUR SPOOL SPECIFICATIONS.
9. WIRE MUST BE FREE STRIPPING. THIS IS TO SAY THE INSULATOR IS EASY TO REMOVE FROM THE CONDUCTOR AND THE JACKET IS EASY TO REMOVE FROM THE INSULATORS.
10. WIRE MUST MEET AND BE PRINTED IN WHITE INK WITH THE FOLLOWING APPROVALS:
 - A. U.L. VW-1
 - B. U.L. APPROVAL OR C(UL) APPROVAL
 - C. CSA APPROVAL OR C(UL) APPROVAL
11. WIRE IS TO BE PRINTED IN WHITE INK WITH THE FOLLOWING MARKINGS:
 - A. 300 VOLT
 - B. 18/4
 - C. W1103
 - D. 80 DEGREES CENTIGRADE
12. WIRE OUTSIDE DIAMETER IS CRITICAL: .275 INCHES, +/- .010 INCHES.
13. VOLTAGE RATING IS TO BE 300 VOLTS.
14. TEMPERATURE RATING IS TO BE +80 DEGREES CENTIGRADE.
15. CONDUCTOR INSULATION IS TO BE POLYVINYL CHLORIDE.
16. THE FLEXIBILITY OF THIS WIRE IS CRITICAL. THE BENDING RADIUS SHOULD BE 8 TIMES OR LESS THE CABLE'S OUTSIDE DIAMETER. BENDING RADIUS = 2.2 INCHES. THE MORE FLEXIBLE THE WIRE, THE BETTER.
17. A CERTIFICATE STATING CONFORMANCE WITH OUR SPECIFICATIONS AND THE DATE OF MANUFACTURE NEEDS TO BE SUPPLIED WITH EVERY ORDER OF THIS WIRE.