



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

25-Nov-2013

Product Number : **5151804TFT4.1**

RoHS

**O/A SH CABLE 4/C 18/16 AWG STC
SR-PVC Insulation
Black PVC FT-4 Jacket**

Conductor : 18 AWG 16 Strand STC Cond.	
Total Cable Weight : 76 kg/km	Final Diameter : 0.260 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.75	
Drain : 18 AWG 16 Strand STC Cond.	
DC Resistance 25°C: 6.5 Ohms / 1000 ft	Mutual Capacitance : 42.5 pF/ft
Impedance : 50 Ohms	Cond to Shield Cap. : 76.3 pF/ft
Velocity of Prop : 64 %	Inductance. : 1.2 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C
600V FT-4 (UL) CMG E132883 105°C #18 AWG RoHS

(All of the above values are approximated to within 10%)