



Description: Four 18 AWG Insulated Conductors
 Overall Foil Shield and TPE Jacket

Date: 3/22/2013

JM Part Number: JM56855
Reference: 1804COFS-0JM

Component Four 18 AWG Insulated Conductors

Conductor: 18 AWG, 19/30 tinned copper

Insulation: .016" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .090"

Cable Construction

Cabling: Four conductors cabled together with FR PP Fillers as needed

Drain Wire: 20 AWG, 10/30 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .072" nominal wall of Black TPE .365"

Color Code

1. Red 2. Black 3. White 4. Green

Print

E66440 4/C 18 AWG 93 AWM 20626 90C 600V --- LL41103 GSA AWM
 I/II A/B 90C 600V FT4 --- CE ROHS

Note: Sequential footage markings included

Requirements

Temperature: 90°C
 Voltage: 600V

Approvals: UL AWM Style 20626
 CSA AWM, FT4
 CE-LVD and RoHS Complaint (2011/65/EU)

Paulo Garcia 3/26/13

Written By:	rjc	3/22/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				