



Description: Four 18 AWG Insulated Conductors
 Overall Foil Shield and TPE Jacket

Date: 8/20/2013

JM Part Number: JM56855-SM
Reference: 1804COFS-0JM1

Component Four 18 AWG Insulated Conductors

Conductor: 18 AWG, 19/30 tinned copper

Insulation: .016" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .090"

Cable Construction

Cabling: Four conductors cabled together with FR PP Fillers as needed

Drain Wire: 20 AWG, 10/30 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Separator: Tissue Tape

Jacket: .072" nominal wall of Black TPE .365"

Color Code

1. Red 2. Black 3. White 4. Green

Print

FLOWMARK VACUUM TRUCKS & SKYMARK REFUELERS E66440 4/C 18 AWG 9
AWM 20626 90C 600V --- LL41103 CSA AWM III A/B 90C 600V FT4 ---
CE ROHS + Sequential Footage Markings

Requirements

Temperature: 90°C
Voltage: 600V

Approvals: UL AWM Style 20626
 CSA AWM, FT4
 CE-LVD and RoHS Complaint (2011/65/EU)

Written By:	rjc	8/20/2013	Rev. 0	Initial Issue
Revised By:	rjc	6/3/2014	Rev. 1	Added Reference Number
Revised By:				
Revised By:				