

DATA CABLES

LiYCY Multiconductor signal and control cable overall braid DIN Color code



Marking for LiYCY 03150714:
SAB BRÖCKSKES · D-VIERSEN · LIYCY 7 x 0.14 mm² CE

LiYCY is a shielded, multiconductor signal and control cable recommended for use in European designed computer, data transmission and office equipment, process control and instrumentation, where additional EMI protection is required.

Construction:

Conductor:	bare copper strands with reference to DIN VDE 0812
Insulation:	PVC, Y12 acc. to DIN VDE 0207 part 4
Color code:	with reference to DIN 47100
Stranding:	in layers
Wrapping:	PETP foil
Screen:	tinned copper braiding
Jacket material:	PVC, YM1 acc. to DIN VDE 0207 part 5
Jacket color:	gray

Outstanding features:

- ▶ good EMC characteristic
- ▶ flexible
- ▶ small outer diameter
- ▶ small bending radius

Technical data:

Peak operating voltage:	< 24 AWG = max. 350 V ≥ 24 AWG = max. 500 V
Testing voltage:	< 24 AWG = 800 V ≥ 24 AWG = 1200 V
Min. bending radius	
<i>fixed installation:</i>	5 x O.D.
<i>free movement:</i>	10 x O.D.
Capacitance:	see page N/8
Radiation resistance:	8 x 10 ⁷ cJ/kg
Temperature range	
<i>static:</i>	-30/+70 °C
<i>flexing:</i>	-5/+70 °C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
Oil resistance:	acc. to internal standard, see page N/27
Chem. resistance:	see page N/9
Color code:	see see page N/24
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/28

F
13

item no.	no. of conductors	nominal outer- inch	nominal outer- mm	cable weight ≈ lbs/mt
▶ 20 AWG (≈ 16/32) • 0.50 mm²				
03150150	1	0.126	3.2	13
03150250	2	0.197	5.0	24
03150350	3	0.205	5.2	28
03150450	4	0.220	5.6	34
03150550	5	0.248	6.3	43
03150650	6	0.268	6.8	50
03150750	7	0.268	6.8	52
03150850	8	0.307	7.8	67
03151050	10	0.346	8.8	77
03151250	12	0.354	9.0	86
03151450	14	0.370	9.4	96
03151650	16	0.390	9.9	109
03151850	18	0.417	10.6	128
03152050	20	0.437	11.1	140
03152150	21	0.457	11.6	151
03152450	24	0.496	12.6	167
03152550	25	0.504	12.8	172
03152750	27	0.504	12.8	181
03153050	30	0.520	13.2	197
03153250	32	0.539	13.7	209
03153650	36	0.559	14.2	231
03154050	40	0.622	15.8	280
03154250	42	0.622	15.8	288
03155050	50	0.669	17.0	327
03155250	52	0.669	17.0	336
03156150	61	0.709	18.0	380

item no.	no. of conductors	nominal outer- inch	nominal outer- mm	cable weight ≈ lbs/mt
▶ 19 AWG (≈ 23/32) • 0.75 mm²				
03150175	1	0.138	3.5	15
03150275	2	0.220	5.6	30
03150375	3	0.240	6.1	38
03150475	4	0.260	6.6	46
03150575	5	0.280	7.1	56
03150675	6	0.303	7.7	67
03150775	7	0.303	7.7	69
03150875	8	0.362	9.2	91
03151075	10	0.394	10.0	101
03151275	12	0.413	10.5	123
03151475	14	0.433	11.0	136
03151675	16	0.453	11.5	155
03151875	18	0.488	12.4	177
03152175	21	0.535	13.6	206
03152475	24	0.567	14.4	224
03152775	27	0.579	14.7	244
03153075	30	0.622	15.8	288
03153275	32	0.642	16.3	304
03153675	36	0.665	16.9	333

item no.	no. of conductors	nominal outer- inch	nominal outer- mm	cable weight ≈ lbs/mt
▶ 18 AWG (≈ 30/32) • 1.00 mm²				
03150180	1	0.142	3.6	17
03150280	2	0.228	5.8	34
03150380	3	0.248	6.3	43
03150480	4	0.268	6.8	53
03150580	5	0.291	7.4	65
03150680	6	0.315	8.0	76
03150780	7	0.315	8.0	81
▶ 16 AWG (≈ 27-29/30) • 1.50 mm²				
03150185	1	0.150	3.8	21
03150285	2	0.256	6.5	46
03150385	3	0.268	6.8	53
03150485	4	0.291	7.4	66
03150585	5	0.339	8.6	88
03150685	6	0.366	9.3	104
03150785	7	0.366	9.3	110

Other dimensions and colors are possible on request.