



DESC: 18/6 CABLE 80°C 300V

DWI NO: FCAB186-013

SCALE: 15x

DATE: 11/14/06

DR. BY: Ken D

NWI NO: FCAB186-013


CUSTOMER: INDUSTRIAL ELECTRIC

CUSTOMER P/N: 1806COBS-8NW

| ITEM | SPECS. |
|------|--|
| A. | 18 GAUGE 16x30TC BUNCHED O.D. .049±.003" |
| B. | 9 MILS PVC INSULATION 80°C 300V 7 MILS MIN. PVC INSULATION O.D. .070±.002" |
| C. | POLY FILLER |
| D. | 85% MIN. TC BRAID SHIELD 36 GAUGE SINGLE ENDS |
| E. | 30 MILS TUBED PVC JACKET 80°C 300V 24 MILS MIN. PVC JACKET GRAY JACKET CABLE IS NOT UL OR CSA APPROVED |

NORTHWIRE RESTRICTED

This document contains Northwire, Inc. proprietary data, and is not to be copied, reproduced, used or divulged to unauthorized persons, in whole or in part, without proper authorization in writing from Northwire, Inc. This information is the property of Northwire, Inc. which reserves all rights to it.



ELECTRICAL REQUIREMENTS:
NONE SPECIFIED

MECHANICAL REQUIREMENTS:
NONE SPECIFIED

| | | | | |
|-----------------|-----|----------|----------|----------|
| INITIAL RELEASE | A | 11/14/06 | KAD | |
| REVISION RECORD | REV | REV DATE | APPROVAL | APPROVAL |