



**Description:** Six Conductor, 18 AWG  
 Overall Foil Shield and PVC Jacket

**Date:** 8/5/2014

**JM Part Number:** JM57272  
**Reference:** 1806COFS-8JM

<b>Components</b>	Six 18 AWG Insulated Conductors
Conductor:	18 AWG, 16/30 tinned copper
Insulation:	.016" nominal wall of PVC (see color code) .077"

<b>Cable Construction</b>	
Cabling:	Six insulated conductors twisted together with FR PP Fillers
Binder:	Fleece Tape
Drain Wire:	18 AWG, 16/30 tinned copper
Shield:	Aluminum-Mylar tape, Aluminum side IN
Jacket:	.032" nominal wall of Gray PVC .305" (.321" Max)

<b>Color Code</b>	1. Black	2. Red	3. White	4. Green	5. Orange	6. Blue
-------------------	----------	--------	----------	----------	-----------	---------

**Surface Print - Inkjet**  
 E138031 6/C 18 AWG 105C SHIELDED (UL) TYPE CM OR AWM 2464 80C 300V VW-1  
 --- LL41103 CSA TYPE CMG 50C FT4 --- CE ROHS

<b>Requirements</b>	Temperature: 105C	Approvals: UL Type CM
	Voltage: 300V	AWM Style 2464
		CSA Type CMG
		CE-LVD & RoHS Compliant (2011/65/EU)

Written By:	rjc	7/29/2014	Rev. 0	Initial
Revised By:	scs	8/5/2014	Rev. 1	Added JM and Reference Numbers
Revised By:				
Revised By:				