

# Technical Data Sheet

## RG11/U Type CATV Coaxial Cable



2833 West Chestnut Street  
 Washington, PA 15301  
 Toll Free: (800) 245-4964  
 Fax: (724) 222-6420  
 www.westpenn-wpw.com

<b>PART NUMBER:</b>	<b>821</b>
<b>DESCRIPTION:</b>	RG11/U – 1 Conductor 14 AWG Solid, 100% Al. Foil + 65% Al. Braid and an overall PVC Jacket.
<b>NEC RATING:</b>	CATV/ CL2
<b>APPROVALS:</b>	(UL) Listed
<b>APPLICATION:</b>	Indoor for: – CATV/MATV

### Construction Parameters:

Conductor	14 AWG Bare Copper
Stranding	Solid
Insulation Material	Gas Injected Polyethylene
Insulation Thickness	.280" Nom.
Number of Conductors	1 Center Conductor
Shield	100% Al Foil + 65% Al. Braid
Jacket Material	PVC
Overall Cable Diameter	0.380" Nom.
Approximate Cable Weight	42 Lbs/1M' Nom.
Flame Rating	Article 725

### Electrical & Environmental Properties:

		<u>Mhz</u>	<u>db/100ft</u>
Temperature Rating	-20deg C to 60deg C	5	.23
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	55	.92
Velocity of Propagation	82% Nom.	100	1.20
Impedance	75 ohms Nom.	270	1.92
DC Resistance per Conductor @ 20deg C	2.6 Ohms/1M' Nom.	400	2.4
Jacket Color	Black	550	2.85
RoHS Compliant	Yes	750	3.40
		1000	4.05
		1800	5.90
		2250	6.42
		3000	7.76

### Mechanical Properties:

Max. Recommended Pull Tension	230 lbs.
Min. Bend Radius (Install)	3.8"

### Connectors and Accessories

F Crimp:	CN-F11ALX
F Compression:	CN-FS11V

Specification Issue Date: 7/06

This document is the property of West Penn Wire.  
 The information contained herein is considered  
 Proprietary and not to be reproduced by any means  
 Without written consent of West Penn Wire

Standard Lengths are 1000ft.  
 The Jacket is sequentially footmarked.  
 The information presented here is, to the best of our  
 knowledge, is true and accurate. However, since  
 conditions of use are beyond our control, all  
 recommendations or suggestions are presented  
 without guarantee or responsibility on our part. We  
 disclaim all liability in connection with the use of  
 information contained herein or otherwise.

