

Aerospace Part#: 1751S

PLENUM CABLE

DESCRIPTION

7 Conductors AWG 18/7x26 TC
Unshielded FEP/FEP Gray CL2P CMP Special Color

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
7	18/7x26	Tinned Copper	FEP	.007"	.062"

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.010"	.206" Nom.	4" lay on Cable with Clear Mylar

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 200C	50.84 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage	Capacitance (Cond. To Cond.)	Impedance
UL Rated 300V Power Ltd.	21.2 pf / ft nom.	75 ohms nom.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

MISCELLANEOUS

Markings: E111036 TYPE CL2P - E130356 TYPE CMP 18 AWG (UL), C(UL) 200C FEP / FEP

Color Code: Black / Red / White / Green / White-Black / Blue / Orange /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice