

AEROSPACE WIRE & CABLE, INC.  
129-09 18TH AVENUE  
COLLEGE POINT, NY 11356  
(718) 358-2345  
FAX (718) 358-2522

CABLE SPECIFICATIONS

|                  |   |   |                             |             |
|------------------|---|---|-----------------------------|-------------|
| CUSTOMER         | : |   | SHIP DATE :                 |             |
| PART NUMBER      | : | 1751pv  | QUANTITY :                  |             |
| 1) DESCRIPTION   | : | 7 Cond. Unshd. CL2P CMP 75C ROHS<br>AWG 18/7x26 TC FEP/Aeroflex |                             |             |
| 2) CONDUCTOR     | : | AWG 18/7x26 Tinned Copper                                       | O.D.=                       | .048"       |
| 3) INSULATION    | : | FEP .007" wall  | O.D.=                       | .062"-.064" |
| 4) COLOR CODE    | : | Black / Red / White / Green / Brown / Blue / Orange             |                             |             |
| 5) TWIST LAY     | : | 6" Lay on Cable   |                             |             |
| 6) SHIELD        | : | none  |                             |             |
| 7) BRAID         | : | none  |                             |             |
| 8) JACKET        | : | White Aeroflex .012" wall                                       | O.D.=                       | .213" nom.  |
| 9) MARKING       | : | E111036 TYPE CL2P-E130356 TYPE CMP 18 AWG (UL),C(UL)75C         |                             |             |
| 10) CAPACITANCE: |   | n/a   |                             |             |
| 11) WEIGHT       | : | 49 lbs / 1000 feet  |                             |             |
| 12) TEMPERATURE: |   | UL Rated -5 C to 75 C   | VOLTAGE: UL 300V Power Ltd. |             |