

232 Sherman Street Gardner, MA 01440 Phone: 978-632-0900 Fax: 978-630-1872 Visit us on our website; www.dataquidecable.com

8 CONDUCTOR 18 AWG OVERALL BRAID

7 1 2 6 3 3 5 4

CONDUCTORS:

- 18 AWG (19x30) Tinned Coated Copper Insulated with .016" Nominal Wall of PVC to a Nominal O.D. of .080" Singles Manufactured in Accordance with MIL-STD-16878 Type 3 (C)
- 8 Conductors Total
- Color Coded as Indicated

FILLER:

- Polypropylene in Core Area

BINDER:

- .001" Thickness Polyester Tape

BRAID SHIELD:

- 36 AWG Tinned Copper, 90% Nominal Coverage

JACKET:

- .036" Nominal Wall of Gray PVC to a Nominal O.D. of .365" (.375" Max. O.D.)
- Manufacturer's Identification Thread Pulled under Jacket

COLOR CODE

Cond.	Color	Cond.	Color
1	Black	5	Orange
2	White	6	Blue
3	Red	7	White/Black
4	Green	8	Red/Black

AGENCY APPROVAL

- RoHS			

REVISION HISTORY

0	7/22/14	WD	FIRST ISSUE

Customer Number		
D.G. Part Number	94J16-1	
Prepared By: KAM		
Reviewed By: WJD		