

1. CONDUCTOR (2):

- 1.1 Size and Material: 20 7/.0121" AWG nickel-plated copper wire.
- 1.2 O.D.: .036" nom.

2. INSULATION:

- 2.1 Extruded PTFE.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .062" nom.
- 2.4 Color code: white, white/red.

3. CABLING:

- 3.1 The two wires are twisted together.
- 3.2 O.D.: .124" nom.

4. SHIELD:

- 4.1 Braided 36 AWG stainless steel wires.
- 4.2 Coverage: 99.9% nom.
- 4.3 O.D.: .144" nom.

5. PERFORMANCE:

- 5.1 Voltage rating: 300 VAC R.M.S.
- 5.2 Temperature rating: 250°C




6. REFERENCES:

- 6.1 UL Subject 758 (AWM), Style 1815 (inner wires only)
- 6.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B (inner wires only).

CUSTOMER APPROVAL

Sign: _____

Date: _____

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---|--|---|
| Engineering Change Notice No. <table border="1" style="width: 100%; height: 100%; border-collapse: collapse;"> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |  This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited. | Done: <i>Pierre Garand</i> Date: November 27, 2013 Verified: <i>Carroll</i> Date: November 27, 2013 |  1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfd.com Description: 2(XE13N207/0121)W 9-92/9 100%K |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| UNCONTROLLED DOCUMENT A later revision of this specification may exist. |  A member of The Marmon Group of companies | Size: A Scale: --- Page: 1 of 1 | Code Ident. No: 57104 Specification No.: Q03830-S Rev. --- | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |