

232 Sherman Street Gardner, MA 01440 Phone: 978-632-0900 Fax: 978-630-1872 Visit us on our website; www.dataquidecable.com

18 CONDUCTOR 18 AWG PVC INSULATED CABLE UNSHIELDED WITH PVC JACKET

CONDUCTOR:

- 18 AWG 16 Strands Tinned Annealed Copper in Accordance with ASTM B-3 and B-8

DIELECTRIC:

- .016" Nominal Wall Thickness Thermoplastic PVC to Diameter of .078"

COLOR CODE:

- As Indicated

CABLE ASSEMBLY:

- Lay Length: 6" Nominal Left Hand Direction
- Filler: Polypropylene
- Binder: .001" Thickness Nonwoven Tissue Tape

JACKET:

- Material: Thermoplastic PVC
- Extrusion Method: Pressured
- Color: Black
- Wall Thickness: .065" Nominal
- Finished Cable Diameter: .525" Nominal +/- .015"

CABLE IDENTIFICATION:


- Type: Manufacturer's Identification Thread Pulled under Jacket

MECHANICAL:

- Operating Temp.: -30C to +105C
- Voltage: 600V RMS

3/07/14 CRAI

	1	
Customer Number		
D.G. Part Number	13J6-4	
Prepared By: KAM		
Reviewed By: WJD		



COLOR CODE

Cond.	Cond. Color		Color
1	WHITE	10	BLUE/WHITE
2	TAN	11	GREEN
3	PINK	12	GREEN/WHITE
4	GRAY	13	RED
5	VIOLET	14	RED/WHITE
6	YELLOW	15	BLACK
7	BROWN	16	BLACK/WHITE
8	BROWN/WHITE	17	ORANGE
9	BLUE	18	ORANGE/WHITE

AGENCY APPROVAL

- RoHS

REVISION HISTORY

0	9/12/13	WD	FIRST ISSUE
1	1/9/14	WD	INCREASE JKT WALL/FINAL O.D.
2	3/7/14	WD	ADD COLOR CODE