DGC DATA GUIDE CABLE
SPECIALTY & CUSTOM CABLES

232 Sherman Street Gardner, MA 01440
Phone: 978-632-0900 Fax: 978-630-1872
Visit us on our website; www.dataguidecable.com

18 AWG 20 CONDUCTOR PVC/PVC UNSHIELDED CABLE

CONDUCTORS
(20 TOTAL):
- 18 AWG 16 Strands Tinned Overcoat Copper in Accordance with ASTM B-8 and B-33

DIELECTRIC:
- .010" Nominal Wall Thickness PVC to a Diameter of .067"

COLOR CODE:
- As Indicated

CABLE ASSEMBLY:
- Lay Length: 5" Nominal Left Hand Direction
- Filler: None Required
- Binder: .001" Nominal Thickness Polyester

JACKET:
- Material: PVC
- Color: Allen Bradley Gray
- Wall Thickness: .053" Nominal
- Finished Cable Diameter: .450" Nominal

CABLE IDENTIFICATION:
- Type: Surface Print on Jacket
- Ink Color: Black
- Legend: "E201454 18AWG TYPE ITC (UL) 90C OR AWM 2464 80C 300V VW-1-- LL91737 CSA TYPE CMG 90C"

Customer Number	1820C-8DGA
D.G. Part Number	97M22-2
Prepared By: LLJ	
Reviewed By: WJD	

COLOR CODE

CONDUCTOR	COLOR
1	BLACK
2	WHITE
3	RED
4	GREEN
5	ORANGE
6	BLUE
7	WHITE/BLACK
8	RED/BLACK
9	GREEN/BLACK
10	ORANGE/BLACK
11	BLUE/BLACK
12	BLACK/WHITE
13	RED/WHITE
14	GREEN/WHITE
15	BLUE/WHITE
16	BLACK/RED
17	WHITE/RED
18	ORANGE/RED
19	BLUE/RED
20	RED/GREEN

LISTINGS/AGENCY APPROVAL

- UL SUBJECT 2250 TYPE ITC 90C
- UL AWM 2464 80C 300VOLTS
- CSA TYPE CMG 90C
- RoHS

REVISION HISTORY

-	2/23/99	WJD	INITIAL RELEASE
1	1/9/08	WJD	ADD ROHS COMPLIANCE
2	5/9/18	WJD	REFORMAT-RE-RELEASE