

1. CONDUCTOR:

- 1.1 Size and Material: 20 7/28 AWG nickel-plated copper wire.
- 1.2 O.D.: .038" nom.

2. INSULATION:

- 2.1 Extruded PTFE.
- 2.2 Marking on the insulation: not required as per UL Standard.
- 2.3 O.D.: .092" ± .002"
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 250°C






4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 1911.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No. <table border="1" style="width: 100%; height: 100%; border-collapse: collapse;"> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table>																																																																	 This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done:  Date: August 29, 2012 Verified:  Date: August 29, 2012	 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfd.com Description: XE27N207/28-X
UNCONTROLLED DOCUMENT A later revision of this specification may exist.	 A member of The Marmon Group of companies	Size: A Scale: --- Page: 1 of 1	Code Ident. No: 57104 Specification No.: F00232-X Rev. ---																																																																