

**1. CONDUCTOR:**

- 1.1 Size and Material: 20 19/0073" AWG nickel-plated copper wire.
- 1.2 O.D.: .035" nom.

**2. INSULATION:**

- 2.1 Extruded PTFE.
- 2.2 Marking on the insulation: not required as per UL Standard.
- 2.3 O.D.: .083" min./0.089" nom./0.093" max.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 250°C




**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 1911.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

<b>Engineering Change Notice No.</b>							 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfd.com</p>			
1574	1749	1989						Date: May 21, 2013					
								Verified: <i>Pierre Garand</i>		Description: <b>XE27N2019/0073-X</b>			
								Date: May 21, 2013					
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>	Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F00235-X</b>