1. CONDUCTOR:

1.1 Size and Material: 22 AWG, 7 strands, nickel-plated copper wire.

2. INSULATION:

- 2.1 Extruded PTFE.
- 2.2 Wall thickness: .038" nom.
- 2.3 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

3.1 Voltage rating: 30 KVDC 3.2 Temperature rating: 250°C

4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 1911.

CUSTOMER APPROVAL

Sign: _____ Date:

Engineering Change Notice No.									Done: Q C					
1569								OMI	Tierre barand			Harbour		
									Date:	August 20	6, 2008			
								This specification is the property of Harbour Industries Canada Limited and may not be used or	Verified: Carris atte		1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com			
								copied without the express written permission of Harbour Industries Canada Limited.			Description: XE38N227/0096-X			
								Harbour muusines Canada Linnieu.	Date: August 27, 2008					
							NIT	MARKON	August 27, 2000		7,2000			
A later revision of this specification may exist.								A member of The Marmon Group of companies	Size:	Scale:	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F04839-X	Rev.
													Wire & Cable Speci	ication - HBR.04.86.D