

**15A, 20A** | Plugs/Connectors, Flanged Inlets/Outlets

**Residential Grade Plugs and Connectors, Flanged Inlets and Outlets**

**2-Pole, 3-Wire, Grounding Plugs and Connectors**

Rating		15A-125V	15A-125V		
NEMA					
		5-15P	5-15R		
Description	Color	Cat. No. Plug	Cat. No. Connector	Wire Gauge (stranded)	Cord Dia. (Inches)
Grounding Plug and Connector Clamptite Hinge	White	3W101-W	3W102-W	AWG SJ 16/3	0.325"-0.360"
	Gray	3W101-GY	3W102-GY	—	—
	Black	3W101-E	3W102-E	—	—
	Orange	3W101-OR	3W102-OR	—	—
Vinyl Handle Plug with cord clamp	Black	48648-E	—	18-14	.437" max
Vinyl Connector with steel cord clamp	Black	—	617	20-16 max	.437" max
Rubber Plug and Connector with vinyl inner assembly	Black	113	114	18-14	.396"-.562"
Weatherproof Inlet on Flush Mount Wallplate with aluminum cover	—	4937	—	#10 max. copper or copper clad	—

Cross Reference to page B-46 for Side Wired, Non-Grounding Single (Double Swipe) Receptacle 5032 with matching plug 9151-N



3W101-E



113



114



4937