

# Straight Blade Devices

## 2 Pole, 3 Wire Grounding

15 and 20 Ampere, 125 Volts

### INSULGRIP® Heavy Duty Plugs



**IP20**  
SUITABILITY



NEMA 5-15P  
15A 125V  
UL CSA  
0.5 HP



NEMA 5-20P  
20A 125V  
UL CSA  
1 HP

#### Insulgrip Plugs

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	<b>HBL5266C™</b>	<b>HBL5366C™</b>
Corrosion resistant yellow nylon.	.230"-.720" (5.8-18.3)	<b>HBL52CM66C</b>	<b>HBL53CM66C</b>
8-position angle plug, black and white nylon.	.325"-.655" (8.3-16.6)	<b>HBL5266CA</b>	<b>HBL5366CA</b>
8-position angle plug, transparent enclosure.	.325"-.655" (8.3-16.6)	<b>HBL5266CAT</b>	—
Anchor lock, black and white nylon. <sup>(1)</sup>	.230"-.720" (5.8-18.3)	<b>HBL5280C</b>	—
Anchor lock, corrosion resistant yellow nylon. <sup>(1)</sup>	.230"-.720" (5.8-18.3)	<b>HBL52CM80C</b>	—
Finger grip, black neoprene, combination screws. CSA only.	.312"-.468" (7.9-11.9)	<b>HBL5921</b>	—
Fusible, black vinyl housing, slotted screws. CSA only.	.296"-.625" (7.5-15.9)	<b>HBL5299</b>	—

#### Insulgrip Hospital Grade Plugs

Description	Cord Dia.	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	<b>HBL8215C™</b>	<b>HBL8315C</b>
Transparent housing.	.230"-.720" (5.8-18.3)	<b>HBL8215CT</b>	<b>HBL8315CT</b>
8-position angle plug, transparent housing.	.250"-.655" (6.4-16.6)	<b>HBL8215CAT</b>	<b>HBL8315CAT</b>

#### Accessories

Seal-Tite® triple seal, black elastomer cover for Insulgrip® plugs when used in a cord set, and connector bodies when used with flanged inlets.	<b>HBL6017*</b>
Same as above except yellow.	<b>HBL60CM17*</b>
PLUGOUT® Lockout device for Hubbell plugs and others.	<b>HLD</b>

Notes: See page A-39 for accessories. See page A-42 for technical information.

<sup>(1)</sup>UL component listed only. Not for general use applications.

\*IP55 when installed and used properly with mating components.

