



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2000

PRODUCT DATA SHEET

Part No: 61-070

CONSTRUCTION SPECIFICATIONS

Description	Coaxial Cable Precision Video 20 AWG 95% Double Tin Braid
Conductor	20 AWG Solid Bare Copper
Conductor Diameter	0.032"
Insulation Type	Polyethylene
Insulated Conductor Dia.	0.207"
Braid Shield	36 AWG TINNED COPPER BRAID, DOUBLE BRAID 95% COVERAGE
Jacket	PVC
Jacket Thickness	0.025"
Overall Cable Diameter	0.308"
Jacket Print	CSA CMG 20 AWG FT4 C22.2 NO. 214 LL83251 RU AWM STYLE 1354 E111002 PRECISION VIDEO ROHS (WORK ORDER #)

ELECTRICALS

Voltage	CMG; 300V, AWM STYLE 1354; 30V	
Capacitance	20.5 pf/ft	
Characteristic Impedance	75 Ohms	
Velocity of Propagation	66%	
Attenuation	MHz	db/100 FT
	1	0.25
	10	0.78
	100	2.53
	200	3.63
	400	5.23

CERTIFICATIONS AND PHYSICAL PROPERT

CSA Certified	*CSA C22.2 No. 214 Communications Cables	
UL Recognized	*UL 758, Appliance Wiring Material	
Flame Test Rating	CSA FT4	
Temperature Rating	60'C	
ROHS	Compliant	
Cable Weight	95.00	kg/km
Copper Content	57.89	kg/km

Reviewed By: Paul Donovan

Rev. 000

17-Jul-08