

Specification

US North Central 5001 S. Towne Drive New Berlin, WI 53151 800-344-2323

www.IEWC.com

Issue Date: 3/5/2014

Issue: 1

Construction

Description	n: 2 Cond 20	2 Cond 20(7) BC PVC/PVC					
Component:	2 Conduct	ors					
Conductor:	20 7/28 TO	20 7/28 TC to ASTM B 33-74					
Insulation:	0.01"	SR PV	C				0.058"
Color Code:							
	Cond	Cond	Color	Color	Cond	Color	
	1 Black		Red				
Assembly:	2 Conductors Bunched Cabled						0.116"
Fillers Optional Fibrillated Polypropylene for roundness (our option)							0.116"
Jacket:	0.032"	0.032" AWM Jacket Compound					
Jacket Color:	Black						0.183"
Print: E174416 RU AWM 2464 80C 300V 20 AWG LL109360 CSA AWM IA 80C 300V OR TYPE CMG 75C FT4 ROHS							
Specifications:							
UL A	WM - 2464	208	300 Volt	VW-1			
Canadian cUL A	WM - 2464	208	300 Volt	FT-1			
Environmental C EU Directive 20	ompliance 002/95/EC(RoHS):					002/95/FU regarding

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.