

Hueson Wire 38 Sutton Street Northbridge, MA 01534 508-234-6372

www.huesonwire.com

Specification C5351 Rev 2

Issue Date: 6/20/2016

Issue: 1

Construction

Descriptio	n: 2 Cond 20 (10) TC mPPE/ PVC	Diam. (In)
Component:	2 Conductor	rs .	
Conductor:	20 (10/30)	Finned copper Smooth Bunch	0.035"
Insulation:	0.007"	mPPE Automotive Grade ISO-6722 Class B	0.049"
Color Code:			
	Cond	Color	Color
<u> </u>	1 Black	2 Red	
Cable	<u> </u>	<u> </u>	•
Assembly:	2 Conductors Bunched Cabled		0.098"
Jacket:	0.015"	Soft 70A AWM Matt	0.131"
Jacket Color:	Black		0.131"
Print: N	No Print		
Specifications:			
	300 Volt	208	

Environmental Compliance

EU Directive 2011/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65